IJEP 42 (2) : 209-217 (2022) (ISSN : 0253-7141)

Approaches, Properties and Applications of Nanocomposite - A Review

M. Rajamehala[1]*, A. Kaviprabha[1], B. Gopalakrishnan[2] and A. Muthu Kumara Pandian[1]

1. Vivekanandha College of Engineering for Women, Department of Biotechnology, Elaiyampalayam - 637 205, Tamil Nadu, India

2. Annamalai University, Department of Chemical Engineering, Annamalai Nagar - 608 002, Tamil Nadu, India

**Corresponding author, Email: ragamehala@gmail.com; kavipraba99@gmail.com*

Nanocomposite is a solid material where one of the stages has one, a couple of components under 100 nanometer or structure having nano-scale repeat isolates between the qualification arranges that make upto a material. This audit talks about the items, applications and mechanical improvements in polymer, earthenware and metal nanocomposites. It is indicated that polymer nanocomposites and the materials utilized in their creation are industrially accessible and discovering applications in a few enterprises, including car, military and nourishment, due to their improved mechanical, electrical and warm properties. Fired and metallic nanocomposites are at a prior phase of advancement and a basic issue to determine is upgrading the scattering of nanomaterial in the networks.

KEYWORDS

Nanocomposite, Nanomaterial, Earthenware, Metal, Polymer

1. INTRODUCTION

Nanocomposites are composites in which in any event one of the stages shows measurements in the nanometer extend (1 nm = 10^{-9} m) [1]. Nanocomposite materials have risen as appropriate choices to defeat impediments of smaller scale composites and solid, while presenting arrangement moves identified with the control of natural organization and stoichiometry in the nanocluster stage. They are accounted for to be the materials of 21st century in the perspective on having plan uniqueness and property mixes that are not found in customary composites. The general comprehension of these properties is yet to be come to, despite the fact that the main derivation on them was accounted for as ahead of schedule as 1992 [2,3]. The quantity of distributed papers containing words, for example nanoscience, nanotechnology, nanomaterial and so on. Explicit gatherings and exceptional issues of certain diaries have been dedicated solely to the rising science and innovation of nanomaterials [4]. It has been accounted for that adjustments in molecule properties can be seen when the molecule size is not exactly a specific level, called 'the basic size' [5]. Furthermore, as measurements arrive at the nanometer level, cooperations at stage interfaces become to a great extent improved and this is essential to upgrade materials properties. In this specific circumstance, the surface territory/volume proportion of support materials utilized in the arrangement of nanocomposite is pivotal to the comprehension of their structure–property connections. Further, revelation of carbon nanotubes (CNTs) in 1991 and their consequent use to create composites showing a portion of the novel CNT related mechanical, warm and electrical properties included another and fascinating measurement to this territory [6,7]. The probability of turning CNTs into composite items and materials made further advances for the preparing and utilizations of CNT-containing nanomaterial. These days, nano-composites offer new innovation and business open doors for all parts of industry, notwithstanding being natural agreeable [8].

As on account of micro-composites, nanocomposite materials can be grouped, as indicated by their lattice materials, in three distinct classes as appeared in table 1 : ceramic network nanocomposites (CMNC), metal network nanocomposites (MMNC) and polymer network nanocomposites (PMNC). A few strategies have been produced for the arrangement of polymer nanocomposite. The most significant procedures are: intercalation of the polymer, in-situ intercalative polymerization, liquefy intercalation, direct blend of polymer and particulates, layout combination, in-situ polymerization and sol-gel process. Intercalation forms is utilized for readiness of polymer-based nanocomposite, which contain layered silicates, as appeared in figure 1. In this strategy, a dissolvable is utilized in which the polymer or pre-polymer is solvent and the silicate layers are swellable. Nanocom-posites arranged with this technique have structures extending from intercalated to peeled, contingent upon the level of infiltration of

© 2022 - Kalpana Corporation

Table 1. *Processing methods for ceramic nanocomposite*

Method	System	Procedure
Powder process	Al_2O_3/SiC	i) Selection of raw materials [mostly powders - small average size, uniformity and high purity]; ii) Mixing by wet ball milling or attrition milling techniques in organic or aqueous media; iii) Drying by heating, using lamps and/or ovens, or by freeze-drying; iv) consolidation of the solid material by either hot pressing or gas pressure sintering or slip casting or injection moulding and pressure filtration.
Polymer process	Al_2O_3/SiC/SiC	Mixing a Si-polymeric precursor with the matrix material gives pyrolysis of the mixture using a microwave oven, generating the reinforcing particles
Sol-Gel process	SiO_2/Ni, ZnO/Co, TiO_2/Fe_2O_3, La_2O_3/TiO_2, Al_2O_3/SiC, TiO_2/Al_2O_3, Al_2O_3/SiO_2, Al_2O_3/SiO_2/ZrO_2, TiO_2/Fe_2TiO_5, $NdAlO_3$/Al_2O_3	Hydrolysis and polycondensation reactions of an (in)organic molecular precursor dissolved in organic media. Reactions lead to the formation of three dimensional polymers containing metal-oxygen bonds (sol or gel) → dryingto get a solid material and further consolidation by thermal treatment.




Figure 1. *Intercalation of polymers*

the polymer chains into the silicate exhibitions [5,9]. Nanocomposite frameworks, incorporating those fortified with CNTs, have been broadly examined since the 1990s and in like manner, there has been a relentless and ceaseless increment in the quantity of productions regarding the matter, including surveys now and again [2,10,11]. Disregarding this development, most of the audits portray the present status of just one sort of nanocomposite. Therefore, there are just two audits on CMNC and three on CNT-fortified nanocomposite and a very enormous number on PMNC [9,12,13]. On account of PMNC, audits manage handling viewpoints, including those on layered silicates leading and biodegradable polymer-based frameworks fiber fortified and structure/morphology/property angles just as with applications and points of view, remembering key chances and difficulties for the advancement of auxiliary and utilitarian fiber nanocomposite [14,15].

Leading polymer-based composites are novel materials with not exactly a time of history. It is accepted that the absolute control of the entire directing polymer-based composite framework and the improvement of their physical properties (for example electrical conductivity and colloidal steadiness) are yet to be accomplished while both their business accessibility sooner rather than later and a major jump forward for materials science are normal with their suitable use. On account of biodegradable polymer-based nanocomposite, late advancements in planning, portrayal and properties, including crystallization conduct and soften rheology, of both the grid and the layered (montmorillonite) nanocomposite have been talked about. Additionally, an accentuation on strength and interfacial holding among CNTs and polymer lattices is basically disks to underline the pressure move from the framework and the capability of these composites for conceivable large scale CNT-polymer creation. Here, issues experienced so far are considered and implies given in regards to a basic volume part of CNTs to get suitable fortifying (as seen in microcomposites); conceivable disappointment instruments in such composites are additionally exhibited. At last, as far as we could possibly know and in perspective on the exceptionally restricted work on metal-based nanocomposite incorporating the ones with CNT fortifications, no audit is accessible to-date on this framework. CNT-based nanocomposite is finding developing uses in ventures running from game and

© 2022 - Kalpana Corporation

Table 2. *Preparing techniques for metal-based nanocomposite frameworks*

Method	System	Procedure
Spray pyrolysis	Fe/MgO, W/Cu	i) Dissolution of the inorganic precursors (starting materials) in a suitable solvent to get the liquid source; ii) Generation of a mist from this liquid source using an ultrasonic atomizer; iii) Use of a carrier gas to carry the mist into a pre-heated chamber; iv) Vapourisation of the droplets in the chamber and trapping with a filter, promoting their decomposition to give the respective oxide materials; v) Selective reduction of the metal oxides to produce the respective metallic materials
Liquid infiltration	Pb/Cu, Pb/Fe, W/Cu/ Nb/Cu, Nb/Fe, Al-C60	i) Mixing of fine reinforcement particles with the matrix metal material; ii) In thermal treatment, the matrix melts and surrounds the reinforcements by liquid infiltration
RSP with ultra-sonic	Al/SiC	Use of ultra-Sonics for mixing and for improving wettability between the matrix and the reinforcements
High energy ball milling	Cu-Al_2O_3	Milling the powders together till the required nano sized alloy is obtained → nanocomposite

recreation to hardware, car and resistance. CNTs are especially appealing because of their great physical properties which often surpass those of the best traditional materials and are presently being fused into a wide scope of polymers. Another car application is electrostatic paint showering. Plastic body boards should be conductive with the goal that the paint is applied equally and again CNTs are beginning to be utilized as an option in contrast to carbon dark or expensive groundwork.

2. MATERIAL AND METHOD

2.1 Raw material

As with microcomposites, CMNC grid materials incorporate Al_2O_3, SiC, SiN and so forth, while metal lattices utilized in MMNC are chiefly Al, Mg, Pb, Sn, W and Fe and an entire scope of polymers, for example vinyl polymers, buildup polymers, polyolefins, forte polymers (counting an assortment of biodegradable atoms) are utilized in PMNC. By and large, the support is in the nanorange size in these materials. Both engineered and normal crystalline fortifications have been utilized, for example Fe and other metal powders, dirt's, silica, TiO_2 and other metal oxides, in spite of the fact that muds and layered silicates are the most well-known [16]. This is so because of their accessibility with exceptionally low molecule sizes and understood intercalation science notwithstanding producing improved properties in any event, when they are utilized at extremely low focuses [9,17,18]. The majority of these fortifications are set-up by known strategies: compound, mechanical (for example ball processing), fume affidavit and so forth.

2.2 Processing method

In spite of their nano measurements, the greater part of the preparing strategies of the three sorts of nanocomposite remains nearly equivalent to in microcomposites. This is likewise evident in any event, for CNT-strengthened composites. Subtleties on these systems are given underneath.

2.2.1 Ceramic matrix nanocomposites : Numerous techniques have been depicted for the planning of clay network nanocomposite [19,20]. The most widely recognized strategies, as utilized for micro-composites, are traditional powder strategy; polymer antecedent course; shower pyrolysis; fume systems (CVD and PVD) and synthetic techniques, which incorporate the sol-gel process, colloidal and precipitation draws near and the format amalgamation. While table 1 records frameworks arranged by a portion of these techniques [21]. A huge assortment of parameters influencing the sol-gel process, for example kind of dissolvable, timing, pH, antecedent, water/metal proportion and so forth. Permit an adaptable control of basic and substance properties of the last oxide materials. As to handling of carbon nanotubes (CNT) - fortified clay nanocomposite, numerous methodologies have been depicted [22-24].

2.2.2 Metal matrix nanocomposites : The most widely recognized procedures for the preparing of metal grid nanocomposite are shower pyrolysis; fluid metal penetration; fast hardening; fume systems (PVD, CVD); electro statement and substance techniques, which incorporate colloidal and sol-gel forms [25,26]. Table 2 records different frameworks arranged by these tech-

© 2022 - Kalpana Corporation

Table 3. *Processing methods for polymer-based nanocomposite systems*

Method	System	Procedure
Intercalation/pre-polymer from solution	Clay with PCL, PLA, HDPE, PEO, PVA, PVP, PVA, etc.	Employed for layered reinforcing material in which the polymer may intercalate. Using a solvent, in which the polymer is soluble and the silicate layers are swellable
In-situ intercalative polymerization	Montmorillonate with N_6/ PCL/PMMA/PU/Epoxy	Encasing of the layered silicate within the liquid monomer or a monomer solution formation of polymer between the intercalated sheets
Melt intercalation	Montmorillonate with PS/ PEO/PP/PVP, Clay-PVPH	Annealing is a mixture of the polymer and the layer is host above the softening point of the polymer. Diffusion of polymer chains from the bulk polymer melt into the galleries between the host layers during annealing
Sol-Gel process	Polyimide/SiO_2; 2-hydroxy-ethyl acrylate (HEA)/SiO_2, polyimide/ silica PMMA/ SiO_2, polyethylacrylate/ SiO_2, polycarbonate / SiO_2 and poly(amide imide)/TiO_2	Embedding of organic molecules and monomers on sol-gel matrices; introduction of organic groups by formation of chemical bond gives the in-situ formation of sol-gel matrix within the polymer and/or simultaneous generation of inorganic/organic networks

niques. Just two reports are found, for instance, on Fe-based nanocomposite arranged by cementing procedures. The first, by Branagan is designated 'devitrified nanocomposite steel' [27]. This was acquired by extinguishing the metallic glass got from a Fe-based composite, trailed by devitrifying the glass forerunner through warmth treatment over its crystallization temperature. This brought about a material indicating a crystalline multi-stage microstructure. The development of nano phases was clarified by the high nucleation recurrence inside the constrained time for development of grains before impingement [28]. So as to clarify the high hardness of these Fe-based nanocomposites, Branagan and Tang examined novel nanostructures acquired in mass Fe combinations by structuring amalgam organizations with various measures of W and C to get most extreme solvency [28]. Challenges have been experienced in getting ready composites with extremely fine particles because of their incited agglomeration and non-homogeneous dispersion. Utilization of ultrasound improved the wettability between the grid and the particles. Various CNT-fortified MMCs have been combined by various procedures since the primary report in 2002 [29].

2.2.3 Polymer matrix nanocomposites : Numerous strategies have been depicted for the arrangement of polymer nanocomposites, including layered materials and those containing CNTs [30,31]. The most significant ones are: intercalation of the polymer or pre-polymer from arrangement, in-situ intercalative polymerization, dissolve intercalation, direct blend of polymer and particulates, layout blend, in-situ polymerization and sol-gel process. Productions managing different strategies for the fuse of nano-dispersoids into leading polymers are likewise accessible the most noticeable one is presumably the consolidation of inorganic structure hinders in natural polymers [32-34]. Table 3 shows the methodology received in a portion of these procedures intercalative procedures utilized for the planning of polymer based nanocomposites, including those containing layered silicates, are it might be noticed that, in this technique, a scope of nanocomposites with structures from intercalated to peeled can be acquired, contingent upon the level of entrance of the polymer chains into the silicate displays. Thus, this strategy has gotten standard for the arrangement of polymer-layered silicate mixes. The arrangement of CNT-fortified polymer nanocomposites is for the most part performed by various techniques, including direct blending, arrangement blending, liquefy blending and in situ polymerization. These, as pertinent to different frameworks [35,36].

2.2.4 Limitations and process improvements : One of the serious issues when preparing nanocomposites is the total of nanoparticles, which is trailed by insufficient scattering in the ideal definitions. The agglomeration and accumulation happens due to speciûc surface territory and volume impacts [37]. To portray the scattering quality, there are various systems utilized for structure portrayal of nanocomposites, naming X-beam diffraction (XRD), examining electron microscopy (SEM), transmission electron microscopy (TEM), infrared spectroscopy (IR) or nuclear power microscopy (AFM) [38]. For nanoparticles, TEM is the favoured strategy to analyze the scattering since polymer structure, void size and shape, filler size, shape and appro-

© 2022 - Kalpana Corporation

priation, neighborhood crystallinity just as precious stone size can be resolved. The level of intercalation or shedding for particles displaying a specific layered association, for example dirt's can be described by XRD and little point neutron dissipating can be utilized to portray the fractal association of undefined particles, like smoldered silica [39]. At long last, ongoing endeavors have been accounted for to screen nanoparticles scattering and nano-covering thickness circulation inline during their preparing [40].

2.2.5 Scattering quality and reaggregation : Molecule surface modification the vast majority of the inorganic minerals has hydrophilic surfaces and are in this way not good with for the most part hydrophobic polymer frameworks. The point of fillers surface modification is thus their hydrophobization to improve their similarity with the polymer so as to empower intercalation or peeling. The subsequent organophilic and hydrophobic dirt's, the layers of which have lower surface vitality, add to polymer dispersion between the layers and finally earth platelets delamination [41]. This presentation of natural coatings can be done utilizing physical and substance associations among filler and modifier. Physical strategies are performed either with low atomic weight surfactants or high sub-atomic weight polymers. Surfactants by and large incorporate in any event one polar gathering and an aliphatic chain. The modification depends on particular retention of the polar gathering to the high vitality surface of the fillers particles [42]. This trade of inorganic surface cations with natural cations has been generally utilized for surface modifications of inorganic dirt's and routinely acknowledged with long-chain alkyl ammonium salts. Another trademark model is the treatment of calcium carbonate with stearic corrosive, shaping a fundamental salt and diminishing the fillers surface strain and consequently influencing the composite properties [43].

The other procedure shows a filler embodiment with preformed or in-situ-shaped polymers, created by arrangement or emulsion polymerization, individually. To dodge modifier desorption from the molecule surface, covalent bonds showing compound systems can be utilized to improve interfacial connections between the filler and network. Synthetic surface modifications are basically accomplished by means of coupling specialist medicines, such as silane titanate and zirconate to improve the attachment between the polymer and particles, albeit here less data is accessible for nano-particles than for microfillers. Concoction joining of macromolecules onto inorganic particles can be accomplished through covalent holding with the hydroxyl bunches on the unmodified molecule surface [42]. Contrasted with surfactants and coupling operators, this strategy shows a few points of interest because of a more extensive determination of uniting monomers, empowering a customized nanocomposite organizing. Next to ordinarily utilized modifications with alkyl ammonium particles (basically utilized for muds), propelled surface modifications of the fillers incorporate modifications with receptive gatherings, initiator atoms or monomer particles and a few others draws near [41].

2.2.6 Ultrasonic motions : Extra improvement of nanocomposite scattering quality can be accomplished by means of ultrasonic treatment. Ultrasonic cavitation moves high measures of vitality, having the option to upset physical and substance communications. Thusly, it has been broadly utilized for scattering, emulsifying, pounding and initiating particles [44]. Also, ultrasound vitality can break C–C bonds, prompting long-chain radical's arrangement. Those radicals may assemble substance bonds on the earth surface in nanocomposite frameworks and therewith upgrade the polymer/filler similarity yet in addition that of immiscible polymers when all is said in done. There are a few examinations on the utilization of ultrasonic motions for nanocomposite arrangement utilized high power ultrasound to separate silica agglomerates in ethylene propylene diene monomer elastic (EPDM), significantly decreasing the agglomerate size [45,46].

2.3 Utilizations of polymer nanocomposites

2.3.1 Packaging : Barrier materials as showed the most examined and promising materials used to improve the boundary properties of polymeric nanocomposites bound to bundling are layered nanomaterials. Two main types of layered nanomaterials have been studied as nanofillers to decrease the permeability to gases of polymers: layered silicates, (for example nano-clays) and graphene based materials (graphene and graphene oxide). Nano-clays have been widely examined in the course of the most recent decades as a result of their amazing boundary properties, low cost and nourishment contact similarity [47]. The utilization of graphene in nanocomposites is considerably later, however, a few models in writing have indicated that it tends to be a solid possibility for gas-hindrance materials [48]. A portrayal of the most delegate polymeric nanomaterials for bundling dependent on these two kinds of layered materials is appeared in the accompanying sections.

2.3.2 Dirt nanocomposites : By a wide margin the most read nanoscale fillers for polymeric nanocomposite bound to bundling are nanoplatelets made out of muds or other silicate materials. Nano-clays notoriety's for

© 2022 - Kalpana Corporation

bundling application is because of their minimal effort, dependability, adequacy and generosity. Montmorillonite [$(Na, Ca)_{0.33}$ $(Al, Mg)_2$ $(Si_4O_{10})(OH)_2 \cdot nH_2O$)], a layered phyllosilicate made out of anisotropic layers isolated by water atoms, is the average mud utilized for polymeric nanocomposite. The platelets have a normal thickness of ~1 nm and sidelong measurements extending from many nanometers upto a few microns. Every platelet contains a layer of magnesium or aluminum hydroxide octahedral sandwiched between two layers of silicon oxide tetrahedral. Each face of the platelet has net negative charge, which is remunerated by interlayer cations (Ca^{2+}, Mg^{2+}, Na^+ and so on).

Singular layers of montmorillonite have surface territories more than 750 m^2/g and perspective proportions in the request for 100–500 [39]. These basic qualities add to the superb utility of montmorillonite as nanofiller in composites, fundamentally expanding the mechanical and hindrance properties of the polymer with a couple of percent option into the grid. Montmorillonite isn't the main layered silicate utilized in polymeric nanocomposite. Related muds, for example saponite, hectrite and kaolinite have likewise been utilized and have demonstrated properties upgrades [49]. During the most recent two decades, several polymer-earth nanocomposite have been portrayed and nanoclays have been fused into each significant class of polymer, both manufactured and normal.

2.3.2 Graphene based nanocomposites : As of late, graphene has gotten significant consideration and has gotten one of the most contemplated materials because of its prevalent properties. Graphene, a monolayer of graphite, has astounding mechanical, electronic and optical properties yet additionally is viewed as a ultrathin, impeccable two-dimensional (2D) hindrance against gas dissemination [50]. Since the electron thickness of aromatic rings in graphene is sufficiently high to repulse the entrance of iotas or particles. When contrasted and muds, graphene nanoplatelets can have a few favourable circumstances as two-dimensional nanofillers for polymer nanocomposite. Polymers joining graphene show upgraded gas hindrance properties as well as strengthened mechanical quality and improved warm properties and electrical conductivity when appropriately scattered in the polymer grid. As contrasted and other nanocarbon structures, for example fullerenes or carbon nanotubes, graphene have a higher surface-to-volume proportion (perspective proportion) thus will have the option to accomplish the longest gas-dispersion pathway, even at low loadings. The principle disadvantage when utilizing this promising material is that the combination of imperfection free, huge territory, monocrystalline graphene everywhere scales is as yet testing and unreasonably costly for bundling application [51].

One option for the utilization of the gas-obstruction properties of graphene in large scale manufacturing is to utilize graphene oxide (GO) or its diminished structure, decreased graphene oxide. GO, which comprise of oxygen-containing utilitarian gatherings on the basal plane can be delivered everywhere scale in polar solvents and can be well-scattered with high angle proportion in hydrophilic polymers [52]. Polymer nanocomposite are mostly delivered by arrangement blending and dissolve handling. For graphene-nanocomposite the platelet size, stacking direction and level of graphene peeling in the polymer lattice are significant elements influencing the gas transport. Also, the high mechanical quality, warm dependability and electrical conductivity permit brilliant applications. Be that as it may, the total of graphene derivatives at high loadings, the nearby imperfections of nanocomposite during arrangement and the great dispersability in the network are significant impediments to defeat while getting ready graphene-polymer nanocomposite.

As a further extremely positive point of view as far as the utilization of graphene in bundling applications, graphene stores were appeared to have sufficient flexibility to withstand thermoforming. It was likewise exhibited to broaden the time span of usability of brew pressed in PET containers by a factor of 2-5 [53]. In this examination, precious stone, like carbon (DLC) was kept utilizing a microwave plasma reactor to reach nanocoatings in the scope of 50 nm thickness prompting more than 10-crease decline in the oxygen penetration. The optical properties of the covering were accounted for to differ from semi-straightforward to completely straightforward contingent upon the innovation utilized.

2.3.3 Different nanoparticles with potential in bundling applications: Powder qualifies as great support filler of polymeric networks since it is a layered mineral with a high perspective proportion (molecule width/thickness H = 20:1). This is a result of its platy nature, having micron-sized measurements on length and width, with nanometric thicknesses. The size of an individual powder platelet (a couple thousand of rudimentary layers) can fluctuate from around 1 to more than 100 μm, contingent upon the states of center development. Van der Waals' holes (interlayer or exhibition) between the layers are shaped due to stacking, which may aid the delamination conduct of powder particles during the

© 2022 - Kalpana Corporation

mixing with a network. Layer charge is zero or little, as there are not particles present between layers. The impacts of powder on manufactured polymers have been enormous examined. It was shown that powder improves mechanical properties and macromolecular direction of polypropylene [54]. Additionally, a prompted crystalline structure has been accounted for, proposing that powder particles go about as a nucleating specialist for polymer crystallization. Additionally, high angle proportion platelets have been utilized to improve gas boundary properties. Moreover, despite the fact that this is certainly not an essential objective, different nanoparticles, for example pyrogenic silica have likewise been accounted for to improve the boundary properties of the matrices where they are scattered [55]. In spite of the fact that non-platelet, like nanoparticles lead to bring down increment of tortuosity impact, their high specific surface territory may prompt gas adsorption or more all, as here when scattered in PP, they may go about as nucleating operator expanding the crystallization level of the grid which is notable to build boundary properties. Electro showering is an efficient procedure to create nanostructured surfaces and fuse nanofillers into the bundle polymer grid, as appeared in a few distributed investigations. The utilization of EHDP is likewise intriguing for the joining of dynamic substances (for example antimicrobials and cancer prevention agents) inside the bundle polymer framework, for the advancement of dynamic bundling [56,57].

3. CONCLUSION

Taking everything into account, preparing techniques for various kinds of nanocomposites (CMNC, MMNC and PMNC) are accessible, yet a portion of these posture provokes consequently giving open doors for analysts to beat the issues. As the innovation is grown further, polymer, metal and fired nanocomposites are relied upon to assume a basic job in numerous enterprises requiring superior materials which today utilize ordinary composites.

REFERENCES

1. Roy, R., *et al.* 1986. Alternative perspectives on 'quasicrystallinity': Non-uniformity and nanocomposites. *Mater. Letters.* 4(8-9):323-328.
2. Schmidt, D., *et al.* 2002. New advances in polymer/layered silicate nanocomposites. *Curr. Opinion Solid State Mater. Sci.,* 6(3):205-212.
3. Gleiter, H. 1992. Materials with ultrafine microstructures : Retrospectives and perspectives. *Nanostructured Mater.,* 1(1):1-19.
4. Braun, T., *et al.* 1997. Nanoscience and nanotechnology on the balance. *Scientrometrics.* 38(2): 321-325.
5. Kamigaito, O. 1991. What can be improved by nanometer composites? *J. Japan Soc. Powder Metal.,* 38:315-321.
6. Iijima, S. 1991. Helical microtubes of graphitic carbon. *Nature.* 354 (6348) : 56-58.
7. Biercuk, M.J., *et al.* 2002. Carbon nanotube composites for thermal management. *Appl. Physics Letters.* 80(15):2767-2769.
8. Choa, Y.H., *et al.* 2003. Preparation and characterization of metal. 266 (1-2): 12-19.
9. Alexandure, M. and P. Dubois. 2000. Polymer-layered silicate nanocomposites : Preparation, properties and uses of a new class of materials. *Mater. Sci. Eng.,* 28:1-63.
10. Wypych, F., *et al.* 1997. Preparation of nanocomposites based on the encapsulation of conducting polymers into 2H-MoS_2 and IT-TiS_2. *Quimica Nova.* 20 (4): 356-360.
11. Pandey, J.K., *et al.* 2005. Recent advances in biodegradable nanocomposites. *J. Nanosci. Nanotech.,* 5(4):497-526.
12. Sternitzke, M. 1997. Review : Structural ceramic nanocomposites. *J. European Ceramic Soc.,* 17(9): 1061-1082.
13. Gangopadhyay, R. and D. Amitabha. 2000. Conducting polymer nanocomposites : A brief overview. *Chem. Mater.,* 12(7):608-622.
14. Ray, S.S. and M. Okamoto. 2003. Polymer-layered silicate nanocomposites : A review from preparation to processing. *Progress Polymer Sci.,* 28(11): 1539-1641.
15. Pandey, J.K., *et al.* 2005. An overview on the degradability of polymer nanocomposites. *Polymer Degradation Stability.* 88(2):234-250.
16. Fernando, W. and K.G. Satyanarayana. 2005. Functionalization of single layers and nanofibres : A new strategy to produce polymer nanocomposites with optimized properties. *J. Colloid Interface Sci.,* 285 (1):532-543.
17. Theng, B.K.G. 1974. The chemistry of clay organic reactions. Wiley, New York.
18. Ogawa, M. and K. Kuroda. 1997. Preparation of inorganic composites through intercalation of organoammoniumions into layered silicates. *Bull. Chem. Soc. Japan.* 70(11):2593-2618.
19. Thostenson, E.T., Z. Ren and T.W. Chou. 2001. Advances in the science and technology of carbon

© 2022 - Kalpana Corporation

nanotubes and their composites : A review. *Composites Sci. Tech.,* 61(13):1899-1912.
20. Nakahira, A. and K. Niihara. 1992. Structural ceramics-ceramic nanocomposites by sintering method : Roles of nano-size particles. *J. Ceramic Soc. Japan.* 100(4):448-453.
21. Ennas, G., *et al.* 1998. Sol-gel preparation and characterization of Ni-SiO_2 nanocomposites. *J. Non-Crystalline Solids.* 232-234:587-593.
22. Xia, Z., *et al.* 2004. Direct observation of toughening mechanisms in carbon nanotube ceramic matrix composites. *Acta Materialia.* 52(4):931-944.
23. An, J.W., D.H. You and D.S. Lima. 2003. Tribological properties of hot-pressed alumina-CNT composites. *Wear.* 255(1-6):677-681.
24. Kamalakaran, R., *et al.* 2003. In-situ formation of carbon nanotubes in an alumina-nanotube composite by spray pyrolysis. *Carbon.* 41(4):2737-2741.
25. Baker, C., S. I. Shah and S.K. Hasanain. 2004. Magnetic behaviour of iron and iron-oxide nanoparticle/polymer composites *J. Magnetism Magnetic Mater.,* 280 (2-3):412-418.
26. Yoon, E.S., *et al.* 2002. Microstructure and sintering behaviour of W-Cu nanocomposite powder produced by thermochemical process. *Int. J. Refractory Metals Hazard. Mater.,* 20(3):201-206.
27. Branagan, D.J. 2000. **In** powder metallurgy, particulate materials for industrial applications. **Ed** D.E.Alman and J.W. Newkirk. TMS Publication, St. Louis.
28. Branagan, D.J. and Y. Tang. 2002. Developing extreme hardness (>15 Gpa) in iron based nanocomposites. *Composites Part A Appl. Sci. Manufacturing.* 33(6):855-859.
29. Chen, W.X., J.Y. Lee and Z. Liu. 2002. Electrochemical lithiation and de-lithiation of carbon nanotube-Sn_2Sb nanocomposites. *Electrochem. Commun.,* 4(3):260-265.
30. Jimenez, G., *et al.* 1997. Structure and thermal/mechanical properties of poly(E-caprolactone) clay blend. *J. Appl. Polymer Sci.,* 64:2211-2220.
31. Ogata, N., *et al.* 1997 Structure and thermal/mechanical properties of poly(1-lactide) clay blend. *J. Polymer Sci. Part B Polymer Physics.* 35(2): 389-396.
32. Gangopadhyay, R. and D. Amitabha. 2000. Conducting polymer nanocomposites : A brief overview. *Chem. Mater.,* 12(7):608-622.
33. Azioune, A., *et al.* 1999. Adsorption of human serum albumin onto polypyrrole powder and polypyrrole-silica nanocomposites. *Synthetic Metals.* 102 (1-3):1419-1420.
34. Ogasawara, T., *et al.* 2004. Characterization of multi-walted carbon nanotube/phenylethynyl terminated polyimide composites. *Composites Part A Appl. Sci.,* 35(1):67-74.
35. Liu, J., *et al.* 2002. Preparation and characteristic of a new class of silica/polyimide nanocomposites. *J. Mater. Sci.,* 37(14): 3085-3088.
36. Roslaniec, Z., G. Broza and K. Schulte. 2003. Nanocomposites based on multiblock polyester elastomers (PEE) and carbon nanotubes (CNT). *Composite Interfaces.* 10(1):95-102.
37. Kango, S., *et al.* 2013. Surface modification of inorganic nanoparticles for development of organic-inorganic nanocomposites - A review. *Prog. Polym. Sci.,* 38:1232-1261.
38. Ray, S. and M. Okamoto. 2003. Polymer/layered silicate nanocomposites : A review from preparation to processing. *Prog. Polym. Sci.,* 28: 1539-1641.
39. Arora, A. and G.W. Padua. 2010. Review : Nanocomposites in food packaging. *J. Food Sci.,* 75:R43-R49.
40. Bugnicourt, E., *et al.* 2016. Recent prospects in the inline monitoring of nanocomposites and nanocoatings by optical technologies. *Nanomater.,* 6:150.
41. Mittal, V. 2009. Optimization of polymer nanocomposite properties. Wiley-VCH Verlag GmbH and Co., Germany.
42. Rong, M.Z., M.Q. Zhang and W.H. Ruan. 2006. Surface modification of nanoscale filters for improving properties of polymer nanocomposites : A review. *Mater. Sci. Tech.,* 22:787-796.
43. Fekete, E., *et al.* 1990. Surface modification and characterization of particulate mineral filters. *J. Colloid Interface Sci.,* 135:200-208.
44. Xia, H.S. and Q. Wang. 2003. Preparation of conductive polyaniline/nanosilica particle composites through ultrasonic irradiation. *J. Appl. Polym. Sci.,* 87:1811-1817.
45. Lapshin, S., S.K. Swain and A.I. Isayev. 2008. Ultrasound aided extrusion process for preparation of polyolefin-clay nanocomposites. *Polym. Eng. Sci.,* 48:1584-1591.
46. Isayev, A. I., C.K. Hong and K. J. Kim. 2003. Continous mixing and compounding of polymer/filter and polymer/polymer mixtures with the aid of ultrasound. *Rubber Chem. Tech.,* 76:923-947.
47. Duncan, T.V. 2011. Applications of nanotechnology in food packaging and food safety : Barrier materials, antimicrobials and sensors. *J. Colloid Interface Sci.,* 363.

© 2022 - Kalpana Corporation

48. Ndoro, T.V., *et al.* 2011. Interface of grafted and ungrafted silica nanoparticles with a polystyrene matrix : Atomistic molecular dynamics simulations. *Macromolecules.* 44:2316-2327.
49. Yano, K., A. Usuki and A. Okada. 1997. Synthesis and properties of polyimide-clay hybrid films. *J. Polym. Sci. Part A.* 35:2289-2294.
50. Geim, A.K. and K.S. Novoselov. 2007. The rise of graphene. *Nat. Mater.,* 6:183-191.
51. Huang, P.Y., *et al.* 2011. Grains and grain boundaries in single-layer graphene atomic patchwork quilts. *Nature.* 469:389-392.
52. Suk, J.W., *et al.* 2010. Mechanical properties of monolayer graphene oxide. *ACS Nano.* 4:6557-6564.
53. Casiraghi, C., J. Robertson and A.C. Ferrari. 2007. Diamond, like carbon for data and beer storage. *Mater. Today.* 10:44-53.
54. Castillo, L., *et al.* 2013. Thermoplastic starch films reinforced with tale nanoparticles. *Carbohydr. Polym.,* 95:664-674.
55. Vladimirov, V., *et al.* 2006. Dynamic mechanical and morphological studies of isotactic polypropylene/fumed silica nanocomposites with enhanced gas barrier properties. *Compos. Sci. Tech.,* 66:2935-2944.
56. Wen, P., *et al.* 2016. Fabrication of electrospun polylactic acid nanofilm incorporating cinnamon essential oil/b-cyclodextrin inclusion complex for antimicrobial packaging. *Food Chem.* 196:996-1004.
57. Fabra, M.J., *et al.* 2015. Development of multilayer corn starch-based food packaging structures containing β-carotene by means of the electro-hydrodynamic processing. *Starch/Staerke.* 68:603-610.

© 2022 - Kalpana Corporation