Computer Communications 151 (2020) 419–427

Contents lists available at ScienceDirect

Computer Communications

journal homepage: www.elsevier.com/locate/comcom

Intelligent software defined network based digital video stabilization system using frame transparency threshold pattern stabilization method

Kokila S. [a,*], Ramesh S. [b]

[a] Department of ECE, Vivekanandha College of Engineering for women, Tiruchengode, Namakkal Dt, India
[b] Department of EEE, K.S.R. College of Engineering, Tiruchengode, Namakkal Dt, India

ARTICLE INFO

Keywords:
Video stabilization
Frame transparency threshold pattern stabilization
Local motion estimation
Global motion estimation
PSNR

ABSTRACT

Digital Video Stabilization (DVS) allows the acquisition of video sequences without disturbing jerkiness and removing unwanted camera motion. Many researchers attempt to improve the performance of Digital Video Stabilization but all of them not get perfect results. Therefore in this research work we introduce different DVS strategy that proposes to transfer camera veins to a Frame Transparency Threshold Pattern Stabilization (FTTPS) algorithm. The proposed FTTPS algorithm consists of four steps: (i) Frame Representation; (ii) Motion Estimation; (iii) Filtering and (iv) Compensation. The proposed FTTPS method also utilizes an adaptive criterion for filtering and validation of motion vectors moreover to register a Global Motion Vector (GMV) for each frame, the proposed DVS method satisfactorily assesses the think camera motion by moving an unwanted motion of characteristics. The proposed Frame Transparency Threshold Pattern Stabilization method is basically customized in Matlab programming language, the simulation of the proposed system validated through Inter-Frame Transformation Fidelity (ITF) and Peak to Signal Noise Ratio (PSNR) Values and which is more pragmatic and takes less chip asset and general 93.12% efficiency accomplished utilizing proposed Frame Transparency Threshold Pattern Stabilization system. The suggested digital video stabilization system can be combined with sensible and robot vision, and visual monitoring structures for various low cameras display quality updates.

1. Introduction

Digital video information is actively expanding as of late years depending on the spread of cameras in hand. Such records, however, are typically shakier and have different stereotypes of stitched cameras or cameras shot with machine stabilizers. Digital video stabilization methods to remove the unwanted frame-to-frame shake and hopes to do the unchanging and sound recordings that are super-fast. In phase, digital video stabilization involves three significant improvements, motion prediction, motion impediment, and frame combination, while all said to be performed.

Most of the Existing Digital Video stabilization systems point out the motion disconnection tasks for entire video successions. Regardless, standard video stabilization, for example, is directly in some places on video conferencing and broadcast applications. Moreover, the clients who need to recordings, progressing stabilization can altogether improve the customer required with the offset recordings demonstrated persistently of the viewfinders. The present digital video stabilization has in like manner prepared to decrease the memory necessities with frames offset before pressure. Continuous video stabilization requires that the camera's movement be normal. This camera movement changes a minimum time and how the movement is more troublesome than the result of missing information.

In motion smoothing needs to compel the distinction in-camera motion to guarantee that no block border burst into the offset video frames. The best strategy to bring such necessity into five in an entire problematic issue, especially for online motion smoothing. While the recordings were resting, individuals and cameras moved here to get the best view of the scene that the cameras were deliberately recorded. This goal is called motion and the movement must be kept in motion smoothing.

Deliberately moving the changing rate of the camera's temperament, and a solution may not work properly in the structure of the movement. For example, when the movement of the camera is created, the motion impediment command may reduce enough jerk, and maybe the movement may have deliberately ignored the possibility of off. Likewise, the dynamic movement will have an undefined video offset that deliberately transforms into deliberate observation districts for

* Corresponding author.
E-mail addresses: skokilaece2008@yahoo.com (Kokila S.), rameshs_dr1@yahoo.com (Ramesh S.).

https://doi.org/10.1016/j.comcom.2019.12.048
Received 17 September 2019; Received in revised form 22 December 2019; Accepted 27 December 2019
Available online 7 January 2020
0140-3664/© 2020 Elsevier B.V. All rights reserved.




Fig. 1. Block diagram.

deliberate change. Thus, the motion impediment to being in the right versatility of the procedure. In this work to propose a Frame Transparency Threshold Pattern Stabilization strategy. The FTTPS strategy comes with a steady speed sample filter-based motion impediment.

This work is sorted out as takes after: Section 2 describes past motion smoothing methods and related estimation foundation. Section 3 shows the proposed video stabilization method, followed by Section 4 discuss the results achieved by a proposed system and earlier video stabilization method and finally Section 5 summarizes the conclusion and future enhancement of the proposed digital video stabilization method.

2. Research background

In the current, the researchers have created numerous DVS methods. For each video stabilization strategy, the between frame motion might be modeled utilized two dimensional and three-dimensional models

Regardless, the digital video stabilization may cause a thought or potential logical shuffle to shake when it is poor because the camera is in danger of unpleasant vibrations. In order to defeat this problem, structures for different video stabilization have been carried out to improve the visual thinking of cameras [1–3] in different hands. An automated video stabilization system gyro sensor or accelerator is used to controls the camera vibrations. It uses an inner sensor to control the motion of the movement or the impact of the union to change the light source and the optical center point. In spite of the general, the camera and the optical video stabilizer architecture [4] expanded the volume and spending a camera suit.

The process of video stabilization, which is based on a digital image processing base, usually consists of two stages: exhausted movement (i) to render the camera outlet and (ii) solution frames [5]. The existing video stabilization frameworks can be programmed through camera-based evaluation. The existing two-dimensional (2D) based stabilization systems are used to study the square coordination calculation between legal movement vectors. In [6] assessed the perfect relative model between bordering frames depends on the variable size of the square and [7] proposed a video stabilization calculation utilizing a round square coordinating and Smallest Square fitting.

Since the two-dimensional based procedures can rapidly gauge the camera way, they are associated with various applications [8,9]. In any case, they are sensitive to noise and convey an organizing mistake between picked a frame under the compelling circumstance. An advanced 2D based video stabilization system uses the optical stream to evaluate the regular camera motion. In [10] utilized the Lucas–Kanade visual stream estimation calculation to describe a relative motion appear among frames. In [11–13] proposed to appraise the camera way utilizing the homograph between adjoining structures and smoothed the worldwide way utilizing a Gaussian part.

To upgrade the idea of the balanced out a video, an elective approach used component center around measuring a pivot and scale-invariant camera way. Scale Invariant Feature Transform (SIFT) has been utilized in [14] to facilities using a camera and small squares calculation, using computation to mitigate the computation of the error. In [15–17] utilized headings of SIFT include centers around checking the camera way and restricted an essentialness. The calculation of the quick resurrected section was placed on the calculation of [18,19] calculation of Fast quickened segment test (FQST) video stabilization. In [20] presented motion disclosure utilizing the Random Sample Consensus (RANSAC) and Speeded-up Robust Features (SURF) for video stabilization.

To describe an all the more awesome 2D camera demonstrate, the secretly surveyed camera way is proposed and the video was taken back to improve execution for video stabilization of the 2D camera movement in [21–23]. In [24] introduced a KLT tracker to mitigate the nitty-gritty foundation includes centers. Although 2D video stabilization processes are all fast and reliable under a straight transition application, they neglect to validate the correct camera path in the lower part of the surface. The system has an issue of video stabilization in all the above-discussed methods so in this work proposed Frame Transparency Threshold Pattern Stabilization method to overcome the drawbacks.

3. Proposed materials and method

Fig. 1 explains how to construct a framework for the proposed video stabilization. The structure of the block depends on the determination of the universal camera movement between the two batch frames from the volume movement vouchers that are accessible to the close bit flow. Operation Vector-based global Movement Prediction System If used for this reason. After the parameter of the camera motion of the evaluation, there is softness in the use of the Gaussian channel to conduct the desired movement of the global movement. Finally, the unmatched movement-compensation ends the arrangement of global operating compensation. Each block is depicted on a detailed work beneath.

3.1. Frame separation

The digital video stabilization is a one which plays a noteworthy in the present life which comprising of some frames an arrangement of frames will shape the shots, and the gathering of shots will deliver the scenes, the mix of various views will shape the video. Keeping in mind the end goal to investigations any video, first need to ponder then qualities of the frames and to dissect the properties of the video finishes this to frame change utilizing Matlab. Consider the frames which are changed over from the video by using the Matlab code. Let F (Q) be the Qth frames for input video, where Q will take the qualities from Q = 1, 2, 3 … n, the shot limit. The frame division ventures of FTTPS are talked about underneath

1. Split the given frames into obstructing with n Columns and m rows
2. Figuring the histogram coordinating contrast between the neighboring blocks in sequential frames for a video succession H(i, j, q + 1) and H(i, j, q) remains for the histogram squares at (i, j) in the Kth and $(K+1)$th frames separately the square distinction is estimated by utilizing the following condition

$$D_B(k, k+1, i, j) = \sum_{i=0}^{L-1} \frac{[H(i, j, k) - H(i, j, K-1)]^2}{H(i, j, k)} \quad (1)$$

where D_B = Block Difference

3. Evaluate the histogram distinction between the two back to back frames by

$$D(K, K+1) = \sum_{j=1}^{m} \sum_{j=1}^{n} W ij D_B(k, k+1, i, j) \quad (2)$$

where Wij is the weight of the block at (i, j)

4. Compilation of the entire video differs greatly in different places Distinguished by different types of data which calculates the threshold by the average and graph quality change application. Mean and standard fluctuation can be ascertained by utilizing the accompanying conditions

$$MD = \sum_{k=1}^{n-1} \frac{D(k, k+1)}{n} - 1 \quad (3)$$

$$STD = \sqrt{\sum_{k=1}^{n-1} D(k, k+1) - \frac{(MD)^2}{n-1}} \quad (4)$$

Calculating the collective number of frames

3.2. Local motion estimation

Digital video stabilization has been gained in continuous frames to build second handling means that elimination between features is attached to guarantee parameters that realize the full camera motion. In the beginning, Local Motion Vectors (LMVs) are figured for the first frame amid the procedure for motion estimation. LMVs speak to the contrast between two continuous frames. In this manner, LMVs incorporates both the deliberate and the jitter motion of the camera. This procedure is helpful over the other two phases as far as time complexity. In this way, the fundamental point is first to ascertain nearby outrageous are distinguished. Nearby maxima are associated with by-line to shape the upper envelope. Furthermore, the same type of system to use the low-envelope was taken after the neighboring refinance. Each of the data is between the top and bottom casing. The contrast between the data x (t) and m1 is the primary segment of k1, at that point

$$K1(t) = x(t) - m1(t) \quad (5)$$

$$m1(t) = [U(t) + L(t)]/2 \quad (6)$$

where,
U (t) = Maxima range in local
L (t) = Minima range in local

3.3. Global Motion Estimation (GME)

The GME is used to recognize the Smooth and harsh frames by utilizing flexible thresholds. The loud motion vectors got for two sorts of structures as; still frames with little question motions with fewer features, and brutal frames with vast protest motion with more features. As the motion vectors are figured using direct pixel-based methodology, which considers the entire frame without a moment's delay, so in this work, the higher estimation of the smoothing parameter is kept up the visual quality. To recognize the noisy motion vectors of modestly smoother frames, select the threshold of Global Motion Vectors GMV (t) adaptively.

$$Mean(GMV^x(t)) < th1 \quad (7)$$

To distinguish the noisy motion vectors of moderately harsh frames, adaptively set the threshold of global motion vectors GMV(t) as

$$GMV^x(t) > th2 \quad (8)$$

where the threshold th1 and th2 are defined as

$$th1 = Min(GMV^x(t)) + 0.45 * Mean(GMV^x(t)) \quad (9)$$

$$th2 = 0.45 * Max(GMV^x(t)) \quad (10)$$

Thus the average Mean(GMV^x (t)) and the minimum Min(GMV^x (t)) estimations of the assessed GMV is utilized to figure the thresholds.

3.4. Unwanted motion estimation

A normal motion approximation comprises two important fragments: a deliberate motion part and an unexpected motion portion. A reasonable motion amendment design ought to oust the bothersome motion while keeping up the consider motion. The unwanted movement uses a low-pass filter to eliminate part of the wrong moves as the proposed calculation bearing, which the man himself with high back pieces becomes. A Smooth Motion Vector (SMV) has come up with distillation that deliberately takes after the camera progression. The proposed system at first registers SMV as a first-orchestrate auto reversion,

$$SMV(n) = \alpha SMV(n-1) + (1-\alpha) GMV(n) \quad (11)$$

where ($0 \le \alpha \le 1$) and the file n shows the frame number. Parameter α can be considered a non-smoothing factor. Bigger esteem prompts a smoother, yet maybe falsely settled image succession. It is noticed that a settled estimation of α scarcely prompts greatly balanced out image successions. To maintain a strategic distance from the slack of deliberate development, the accompanying adjustment component of α is utilized:

$$Dv(n) = GMV(n) - SMV(n-1) \quad (12)$$

$$TV(n) = GMV(n) - GMV(n-1) \quad (13)$$

$$UMV(n) = GMV(n) - SMV(n) \quad (14)$$

To reestablish the present frame to it is balanced out a position for counterbalance the present frame by gathered bothersome motion vector and AMV is expressed in Eq. (15).

$$AMV(n) = \sum_{i=m}^{n} UMV(i) \quad (15)$$

where m refers to the first frame since the last scene change

3.5. Filtering

The motion prediction vector is a top illustration vector measuring the replacement of the current and last video frame intermediate pixels. In the light of some time interval between two frames, the interval between interpreted vector frames can be translated as camera speed.

The motion filter acts independently in each axis to isolate vector parts that deliberate and unpleasant camera development. The FTTPS configuration has two input sources (Input1, Input2) and one output. FTTPS is classified as input

$$x_1 = \frac{1}{M}\sum_{i=n-M+1}^{n} |GMV_x(i) - GMV_x(i-1)| \tag{16}$$

$$x_1 = \frac{1}{M}\sum_{i=n-M+1}^{n} |GMV_x(n) - GMV_x(n-m)| \tag{17}$$

$$y_1 = \frac{1}{M}\sum_{i=n-M+1}^{n} |GMV_y(i) - GMV_y(i-1)| \tag{18}$$

$$y_2 = |GMV_y(n) - GMV_y(n-m)| \tag{19}$$

where
x1 and x2 = inputs of FTTPS
y1 and y2 = outputs of FTTPS
$GMV_x(n)$ = horizontal element of last frame
$GMV_y(n)$ = vertical elements of last frame
M + 1 = last GMVs Number.

3.6. Smoothing and compensation

In the midst of the motion evaluation process, nine extricated features were simultaneously monitored and directed by motion vouchers. In any case, there are features where the video is focused on motion, and these features include a universal motion vector motion prediction. In this way, these vectors need to get impassive before the movement in a place where moving objects. Characterize the motion vectors of neighborhood features are $V_i = P_i - R_i$, i = 1, 2, 3 … 9 w P_i and R_i are a similar element in a current frame and reference frame individually. As the whole frame is divided into nine sub-districts, the majority of features featured in the background of the full movie area. Subsequently, the neighborhood movement was simulated by a normal computation of neighborhood motion vectors is expressed in Eq. (20)

$$V'G = \frac{\sum_{i=1}^{N} V'i}{N} \tag{20}$$

where N = Number of Frames and to evaluate the Euclidean distance as

$$d_i = |V'i - V'G| \tag{21}$$

Calculate the global motion vector, which sees six volumes of rank and minimum d_i features

$$V_G = \frac{\sum_{i=1}^{N} V'i}{6} \tag{22}$$

where VG = GMV with horizontal and vertical components.

3.7. FTTPS algorithm

This system is a practical procedure for modification. In this approach, each video layout gets partitioned into a large-scale square (gauge: 16 * 16). Massive squares of current edge and past edges are composed on the preface of specific square planning estimation. The overall algorithm steps of the FTTPS is explained below
Step 1: Select the Input Video and Separate to frames
Step 2: Choose a pixel p in the image, you can expect this pixel power to be in between a pixel that needs to be recognized whether this is an interesting point or not.
Step 3: Set the power value esteem
Step 4: It is surrounded by a pixel p 16 pixels a circle
Step 5: To make the first look on the force of hover 13 with Algorithm Quick, pixels 1, 5, 9 and IP. Not clear from the above picture, as many as three less than four of these pixels, the very exciting point of completing the range model will not be available.
Step 6: The off chance that at least three esteems of four pixels on I1, I5, I9, I13 not above or below IP + T, and that point P is not a tricky thing. Dismiss Pixel P as an understandable conspiracy point for this situation. Otherwise, at least three of the pixels, above or below the IP + T are 16 pixels for everyone in the probe that point and see if 12 coterminous pixels fall into the paradigm, then Repeat the procedure for all the pixels in the image




Fig. 2. Flow chart.

Fig. 2 shows the digital video stabilization system by using the FTPPS system. The proposed FTTPS rating metrics are discussed in the following sections.

3.8. Evaluation metrics

The Mean Squared Error (MSE) and Peak Signal to Noise Ratio (PSNR) is used to survey the general differentiation between two frames of the video, conveyed as

$$MSE_{MV} = \frac{1}{N}\sum_{n=0}^{N}[x_r(n) - y_r(n)]^2 \tag{23}$$

where
x_r(n) = Frame of reference video
y_r(n) = Smoothed Video

$$PSNR_{(f_t, f_{t+1})} = 10log10\frac{WHL^2max}{\sum_{x=1}^{W}\sum_{y=1}^{W}[f_t(x,y) - f_{t+1}(x,y)]^2} \tag{24}$$

where
f_t and $f_{(t+1)}$ = two continuous frames of the video
W and H = width and tallness of each frame,
L_{max} = extreme esteem force of the image.

The PSNR metric is conveyed in decibel (dB), a unit at first portrayed to measure sound power on a logarithmic scale. The interframe transformation fidelity (ITF) can be utilized to assess the last stabilization of the technique, communicated as

$$ITF = \frac{1}{N-1}\sum_{k=1}^{N-1} PSNR(k) \tag{25}$$




Fig. 3. GUI screen.

Table 1
Information about the videos.

Video	Frame Rate Per Seconds (FPS)	Frame count	Duration (s)
Peaks	1	18	0.01
Wild life	15	901	30
Shaky car	25	440	29
Foreman	25	291	12
Book	30	1877	75

where
N = Total Number of Frames.

The Data compression ratio is defined as the ratio between the uncompressed size and compressed size

$$CR = \frac{CZ}{UZ} \times 100 \tag{26}$$

where
CR = Compression Ratio
CZ = Compressed Data
UZ = Uncompressed data

4. Results and discussion

The simulation results and performance comparison of the proposed Frame Transparency Threshold Pattern Stabilization (FTTPS) strategy based digital video stabilization system is discussed in this section. The simulation was done using Matlab 2017a software, the GUI screen of the proposed Digital Video Stabilization (DVS) system is demonstrated in Fig. 3, and the Video pleasures and their first frame picture appears in Fig. 4.

Fig. 3 shows the graphical user interface model of the proposed digital video stabilization method using Frame Transparency Threshold Pattern Stabilization (FTTPS) method and their first frame picture appears in Fig. 4.

Fig. 4 demonstrates the primary frame of all simulated video each one of these recordings has distinctive highlights and advancing conditions. The simulated videos comprise a number of frames with an assurance 480 × 360.

Table 1 shows the results of Frame Rate per Seconds, Frame Count and Execution Time. The Sum of Absolute Difference (SAD) evaluates the shakiness of the video by considering two successive frames. The

Table 2
Filtering response.

Video number	Coordinate	Adaptive filtering	ATPS	FTTPS
Peaks	x	0.8341	0.834	0.986
	y	0.9348	1.0659	1.326
Wild life	x	3.2877	3.851	3.97
	y	4.25	6.014	6.235
Shaky car	x	2.30	2.7090	3.06
	y	3.45	4.641	4.752
Foreman	x	1.25	1.56	1.69
	y	1.85	2.30	2.40
Book	x	6.4	7.56	7.81
	y	8.50	11.40	12.03

estimation of picture mass can be set from 0 to 1 as demonstrated by a level of unsteadiness in the video assessed by human perception. The DVS system performance is evaluated based on the Smoothness index, a quantitative evaluation parameter.


$$SI = \frac{1}{(N-1)} \sum_{t=2}^{N} mx|GMV(t) - GMV(t-1)| \tag{27}$$

where
N = The Total Frames
t = frame Number
m = image mass.

Table 2 discusses the filtering response of the DVS system based on various types of filtering techniques with different videos, as compared to all filtering responses the proposed Frame Transparency Threshold Pattern Stabilization (FTTPS) algorithm produce the best result.

Fig. 5 shows the smoothness index response of the digital video stabilization system using different filtering techniques with different videos, as compared to the digital video stabilization method the proposed Frame Transparency Threshold Pattern Stabilization (FTTPS) algorithm produce the best result.

Two usually utilized activities of smoothing index are the Peak Signal to Noise Ratio and Mean Square Error. The MSE esteem speaks to an aggregate squared mistake between the first picture frames and the output form, while the PSNR esteem represents a measure of the peak noise error. The following Table 3 shows the PSNR analysis.



a) First Video



b) Second Video.



c) Third Video



d) Fourth Video



e) Fifth Video

Fig. 4. Video frame.




Fig. 5. Smoothness index of different algorithm.

Table 3
PSNR analysis.

Scenario	Original	Block matching stabilized	ATPS matching stabilized	FTTPS matching stabilized	Improvement in FTTPS (%)	Improvement in ATPS (%)	Improvement in block matching (%)
Peaks	16.78	20.12	22.30	26.62	9.84	5.52	3.34
Wildlife	26.65	28.01	29.70	32.14	5.49	3.05	1.36
Shaky car	18.65	20.80	23.06	25.13	6.48	4.41	2.15
Foreman	28.32	29.60	31.09	32.16	3.84	2.77	1.28
Book	34.064	35.60	37.01	38.92	4.856	2.946	1.53




Fig. 6. PSNR value of different algorithm against all videos.




Fig. 7. Comparison of time complexity.




Fig. 8. Performance comparison.

Table 4
ITF measurement.

Tested video	Original ITF	Stabilized ITF using FTTPS	Increase in ITF
Peaks	12.41	20.56	8.15
Wildlife	16.23	24.76	8.53
Shaky car	15.91	21.23	5.32
Foreman	25.75	27.75	5.19
Book	15.91	21.22	5.31
Average	16.2404	22.706	6.502

Fig. 6 and Table 3 shows the result of PSNR value comparison with different Digital Video Stabilization algorithms. As compared with all stabilization methods the proposed Frame Transparency Threshold Pattern Stabilization (FTTPS) algorithm was delivered the perfect PSNR response.

Fig. 7 shows the execution time of DVS nature conveyed by different methodologies and it exhibits obviously that the proposed FTTPS system has made less time to execute the videos compared with all other methods.

Fig. 8 exhibits the graphical depiction of evaluation estimations like MSE, connection factor and PSNR got for proposed and existing methods. From the outline, the proposed FTTPS methodology passes on better precision compared with other normal techniques. From the above examination played out, the proposed configuration has been evaluated with various parameters and has conveyed important results with all parts of optical properties and characterization.

Table 4 depicts the ITF measure for the proposed digital video stabilization method using three different videos, as compared with the result of original ITF the stabilized ITF value was high. Therefore, the stabilized videos using the FTTPS algorithm appear smoother and more comfortable for viewing.

5. Conclusion

This work presents a technique for Frame Transparency Threshold Pattern Stabilization (FTTPS) to remove unwanted oscillation in digital video stabilization. The proposed FTTPS framework is a computationally useful digital video stabilization curve using motion data. Since some of the motion vectors obtained are not important, multipurpose thresholding has been created to filter the motion vectors in addition to calculating a GMV for each frame. The proposed stabilization system sufficiently evaluates the movement of the camera intentionally by manhandling the properties of the movement of failure using a versatile apparatus and low-quality FTTPS filter of the complexity of global motion vectors. The simulation is about to demonstrate a superior performance for the proposed algorithm with low computational complexity and the proposed scheme can be used appropriately for portable video matching and in addition to the use of video coding applications. Future needs to improve the visual nature of digital video and give a subsequent performance of compression.

Declaration of competing interest

The simulation is about to demonstrate a superior for the proposed algorithm with low computational complexity and the proposed scheme can be used appropriately for portable video matching and in addition to the use of video coding applications. Future needs to improve the visual nature of digital video and give a subsequent performance of compression.

References

[1] T. Kancharla, S. Gindi, A real-time video stabilization algorithm, in: A. Abraham, J.L. Mauri, J.F. Buford, J. Suzuki, S.M. Thampi (Eds.), Advances in Computing and Communications, ACC 2011, in: Communications in Computer and Information Science, vol. 193, Springer, Berlin, Heidelberg, 2011.

[2] M.N. Favorskaya, V.V. Buryachenko, Warping techniques in video stabilization, in: M. Favorskaya, L. Jain (Eds.), Computer Vision in Control Systems-3, in: Intelligent Systems Reference Library, vol. 135, Springer, Cham, 2018.

[3] K.S. Shagrithaya, E. Gurushankar, D. Srikanth, P.B. Ramteke, S.G. Koolagudi, Video stabilization using sliding frame window, in: B. Shankar, K. Ghosh, D. Mandal, S. Ray, D. Zhang, S. Pal (Eds.), Pattern Recognition and Machine Intelligence. Premi 2017, in: Lecture Notes in Computer Science, vol 10597, Springer, Cham, 2017.

[4] Lokesha Hlmg, Somasekhar Reddy, Karra, S. Akhila, A survey on video stabilization algorithms, Int. J. Adv. Inf. Sci. Technol. 31 (2014).

[5] Shuaicheng Liu, Mingyu Li, Shuyuan Zhu, Bing Zeng, Coding flow: Enable video coding for video stabilization, IEEE Trans. Image Process. 26 (7) (2017) 3291–3302.

[6] Lidong Xu, Xinggang Lin, Digital image stabilization based on circular block matching, IEEE Trans. Consum. Electron. 52 (2) (2006) 566–574.

[7] Chongwu Tang, Xiaokang Yang, Li Chen, Guangtao Zhai, A fast video stabilization algorithm based on block-matching and edge completion, in: MMSP 2011 - IEEE International Workshop on Multimedia Signal Processing, 2011, pp. 1–5, http://dx.doi.org/10.1109/MMSP.2011.6093781.

[8] Hung-Chang Chang, Shang-Hong Lai, Kuang-Rong Lu, A robust and efficient video stabilization algorithm, in: 2004 IEEE International Conference on Multimedia and Expo (ICME), Vol. 1, 2004, http://dx.doi.org/10.1109/ICME.2004.1394117, 1. 29-32.

[9] Anli Lim, Bharath Ramesh, Yue Yang, Cheng Xiang, Zhi Gao, Feng Lin, Real-time optical flow-based video stabilization for unmanned aerial vehicles real-time image processing, 2017.

[10] M.J. Smith, A. Boxerbaum, G.L. Peterson, Quinn Roger, Electronic image stabilization using optical flow with inertial fusion, Proceedings of the. IEEE/RSJ on Intelligent Robots and Systems (2010) 1146–1153.

[11] Jaeyoung Yoon 1, Daeho Lee, Real-time video stitching using Camera path estimation and holography refinement, Symmetry 10 (4) (2018) http://dx.doi.org/10.3390/sym100100.

[12] M. Chethan Kumar Naidu, H. Lokesh, P. Ashwathappa, Implementation of a robust video stabilization system on raspberry pi, Int. J. Innov. Res. Adv. Eng. (JIRA) 3 (04) (2016) ISSN 2349-2763.

[13] Chin-Teng Lin, Chao-Ting Hong, Chien-Ting Yang, Real-time digital image stabilization system using modified proportional integrated controller, IEEE Trans. Circuits Syst. Video Technol. (2009).

[14] Sebastiano Battiato, Giovanni Gallo, Giovanni Puglisi, Salvatore Scellato, SIFT features tracking for video stabilization, in: Proceedings - 14th International Conference on Image Analysis and Processing, ICIAP 2007, pp. 825-830. http://dx.doi.org/10.1109/ICIAP.2007.4362878.

[15] Yanhao Zhang, Hongxun Yao, Pengfei Xu, Rongrong Ji, Xiaoshuai Sun, Xianming Liu, Video Stabilization Based on Saliency Driven SIFT Matching and Discriminative RANSAC, IEEE, 2016.

[16] J. Yu, C. Luo, C. Jiang, R. Li, L. Li, Z. Wang, A digital video stabilization system based on reliable SIFT feature matching and adaptive low-pass filtering, in: H. Zha, X. Chen, L. Wang, Q. Miao (Eds.), Computer Vision. CCCV 2015, in: Communications in Computer and Information Science, vol. 547, Springer, Berlin, Heidelberg, 2015.

[17] Damanpreet Kaur, Amanjot Kaur, Video stabilization using hybrid of SIFT and SURF algorithm, Int. Res.-Based J. (ISSN: 2348-1943) 6 (1) (2017).

[18] Sebastiano Battiato, Giovanni Gallo, Giovanni Puglisi, Salvatore Scellato, SIFT Features tracking for video stabilization, J. Image Anal. Process. (ICIAP 2007) (2007) 825–830.

[19] Shumin Liu, Jiajia Chen, Chip-Hong Chang, Ye Ai, A new accurate homography-computation algorithm for portland and fast traffic video analysis, IEEE Trans. Circuits Syst. Video Technol. PP (99) (2017).

[20] Chao Jia1, Brian L. Evans2, Online motion smoothing for video stabilization via constrained multiple-model estimation Jia and Evans, EURASIP J. Image Video Process. (2017).

[21] Huicong Wu, Liang Xiao, Hyuk Jae Shim, Songze Tang, Video stabilization with total warping variation model, IET Image Process. 11 (7) (2017).

[22] Paresh Rawat, Jyoti Singha, Adaptive motion smoothening for video stabilization, Int. J. Comput. Appl. (0975–8887) 72 (20) (2013) 14.

[23] Weiping Yang, Zhilong Zhang, Yan Zhang, Xinping Lu, Jicheng Li, Zhiguang Shi, Real-time digital image stabilization based on regional field image gray projection, J. Syst. Eng. Electron. 27 (1) (2016).

[24] Drahansky, Filip Orsag, Petr Hanacek, Accelerometer based digital video stabilization for general security surveillance systems martin, Int. J. Secur. Appl. 4 (1) (2010).



S. Kokila received B.E Degree in Electronics and Communication Engineering from Periyar University, and M.E degree in Applied Electronics from Anna University, Coimbatore, Tamilnadu, India in 2002 and 2010. Currently she is working as an Assistant Professor in the Electronics and Communication Engineering Department in Vivekanandha College of Engineering for women, Tiruchengode, Namakkal District, and Tamilnadu, India. She is a Research Scholar at Anna University Chennai, in the area of image processing.



Dr. S. Ramesh is currently working as a Professor and Head in the EEE Department at K.S.R College of Engineering, Tiruchengode, Tamil Nadu, India. He received his Bachelor's in Electrical and Electronics Engineering, and his Masters under the faculty of Electrical Engineering from Anna University. He received his Ph.D. Degree from Anna University, in the year 2012 in the area of power systems and Fuzzy logic controller. He has published enormous number of papers in both national , international journals and conferences.